



# Egret ® EPDM foam Tape

# EGEPDM-3

## SECTION 1: DESCRIPTION & BENEFITS

- 3mm high-density closed-cell EPDM foam as carrier
- Coated with special formula of very high tack adhesive
- Laminated with yellow kraft paper easy release liner
- Excellent properties of elasticity, easy to compress
- Outstanding chemical resistance, slip resistance
- Good high temperature resistance
- Stable chemical properties, good corrosion resistance
- Outstanding conformity to uneven surfaces



## SECTION 2: SPECIFICATIONS

Product Characteristics	Performance Data	Test Method
Carrier Color	Black	Visual
Liner Color	Yellow	Visual
Density	≥ 110 KG/m <sup>3</sup>	ASTM D-3575
Peel Adhesion	≥ 5 N/CM	ASTM D-3330
Loop Tack	16 # steel ball	GB/T 4852-84
Tensile strength	16 N/CM	ASTM D3759
Elongation	≥ 140%	ASTM D-3330
Temp Resistance	-30°C~80°C	

## SECTION 3: APPLICATIONS & OTHER DETAILS

- Automotive roof thermal insulation
- Civil building sealing material
- Waterproof material
- Air ducts pipes insulation
- Antiskid material



**Sliced roll width available (or customized):** 10-1600mm

Standard Length: 100-2000mm

**Tolerance:** Thickness: +/- 10%      Width: +/-1.0mm      Length: +/- 0.4m

**Storage:** Indoor storage: -5°C -40°C (humidity: < 80%), cool & dry, free of direct sunlight

**Shelf Life:** 12 months in room temp.

**N.B.** Please keep the operating surface clean, dry, and free of grease or other dirt & dust. So that **Egret Tape** can have a best performance.

**Changzhou Egret Manufacturing Co., Ltd**

No.4, Tongshun Rd, Henglin Town, Changzhou 213101 • China

T: +86 519 8878 9969 Ext. 807      Email: info@egretmfg.com      Website: www.egretmfg.com